


Features

- Receiver Module
- Internal filter for PCM frequency
- Output active low
- Photo detector and preamplifier in one package.
- Meet ROHS Green Product

Applications

- Receiver

Package Dimensions



Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is ± 0.3 mm unless otherwise noted.
3. Specifications are subject to change without notice
4. This drawing is only for indication, not as a basis for the actual structure.



Selection Guide

Part No	Carrie Frequencies	PART	MATERIAL	COLOR
FDI-M4950385R638-WGC-D2.0-10.0	38 kHz	Chip	Silicon	Black
		Compound	Epoxy	Black

Electrical / Optical Characteristics At Ta=25 °C and Vcc=3.0V

Symbol	Parameter	Ratings			Unit	Condition
		Min.	Typ.	Max		
L	Reception Distance	12			m	$\theta=0^\circ$ (Note 1)
		6			m	$\theta=45^\circ$ (Note 1)
Vs	Supply Voltage	2.7	3	5.5	v	-
Icc	Consumption Current			0.6	mA	No signal input
λ Peak	Peak Wavelength		940		nm	
θ_h	Half Angle		45		deg	-
TH	High Level Pulse Width	400	600		us	Note 2
TL	Low Level Pulse Width	400	600		us	

Note :

1. The ray receiving surface at a vertex and relation to the ray axis in the range of $\theta=0^\circ$ and $\theta=45^\circ$.
2. A range from 30cm to the arrival distance. Average value of 50 pulses.

Absolute Maximum Ratings At Ta=25°C

Parameter	Maximum Rating	Unit
Supply Voltage	5.5	V
Supply Current	2.5	mA
Junction Temperature	80	°C
Operating Temperature Range	-25°C to + 85°C	
Storage Temperature Range	-40°C to + 80°C	
Soldering Condition	260°C For 5 Seconds (Note 1)	

Note 1 : 4mm from the bottom

Typical Characteristics (Ta=25°C unless otherwise specified)












Illustration of used terms



Block Diagram



Application Circuit



Reliability Test Items Conditions

Classification	Test Item	Test Conditions	Test hours	Result
Endurance Test	Operation Life	Ta=Under room temperature	1000hrs	0/20
	High Temperature High Humidity	Ta=+65°C±5°C RH=85%	240hrs	0/20
	High Temperature Storage	High Ta=+85°C±5°C	1000hrs	0/20
	Low Temperature Storage	Low Ta=-35°C±5°C Test time=1000hrs	1000hrs	0/20
Environmental Test	Temperature Cycling	-40°C ~+100°C 15min 5min 15min	300 Cycles	0/20
	Thermal Shock	-35°C ~±5°C ~+85°C ~±5°C 5min 10sec 5min	300 Cycles	0/20
	Solder Resistance	Preheating: 120°C-150°C,within 2 minutes. Operation heating : 260°C(Max.),within5 seconds(Max.) 4mm from the bottom		0/20

Judgment criteria of failure for the reliability

Measuring items	Symbol	Judgment criteria for failure
Reception Distance ($\theta=0^\circ$)	L0	Below $S \times 0.7$
Reception Distance ($\theta=45^\circ$)	L45	Below $S \times 0.7$

Note: 1.U means the upper limit of specified characteristics. S means initial value.

2.Measurment shall be taken between 2 hours after the test pieces have been returned to normal ambient conditions after completion of each test.